

# SUZUKI PERFORMANCE NOTEBOOK

Lake Murray, SC

Suzuki Marine

Test Date: 9-20-17



BOAT		ENGINE		OTHER SPECS	
<b>248 Bay</b>		<b>Suzuki DF200ATX</b>		<b>Propeller</b>	
Material	Fiberglass	Engine Type	4-Stroke Inline 4	Material	Stainless Steel
Length	24' 8"	HP	200	Diameter/Pitch	14.75 x 23
Beam	8' 9"	Displacement	174.9 cu. In.	Number of Blades	3
Weight	3000 lb.s	Operating Range	5500-6100	<b>Mounting Height</b>	
Maximum HP	300	Weight	529 lbs	Hole Position	2nd Hole Up
Fuel Capacity	70 gallons	Lubrication	Wet Sump	Jack Plate	Manual 6" setback up 3"
Transom Height	25"	Fuel Delivery	Multi-Point EFI		
Steering	Hydraulic	Ignition	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
<b>RPM</b>	<b>MPH</b>	<b>GPH</b>	<b>MPG</b>	<b>RANGE</b>	Water Conditions	Calm
IDLE	2.3	0.3	7.67	483	Wind Velocity	0-5 mph
1000	4.4	0.7	6.29	396	Air Temperature	80 deg
1500	6.3	1.3	4.85	305	Fuel Load	30 gal.
2000	7.9	1.9	4.16	262	Weight Onboard	2 person Gear & Battery
2500	10.7	2.9	3.69	232		
3000	17.5	3.7	4.73	298		
3500	23.2	5.3	4.38	276		
4000	28.7	6.7	4.28	270		
4500	33.2	8.9	3.73	235		
5000	37.5	12.0	3.13	197		
5500	41.8	16.0	2.61	165		
6000	42.5	17.8	2.39	150		
6100	44.1	14.3	3.08	194		
Results may vary. Range based on 90% fuel capacity.						
					PERFORMANCE SUMMARY	
					Top Speed	44.1 mph
					0-25 Acceleration	6.86 seconds
					Optimum Cruising	@ 3000 RPM
					Range	298 Miles
					Best Cruising	@ 3000 RPM
					Fuel Efficiency	4.73 MPG

**FOR MORE INFORMATION, CONTACT:**

SeaPro Boats  
Whitmire, SC  
803-694-2644  
<http://www.seapromfg.com>

Suzuki Marine  
[www.suzuki.com](http://www.suzuki.com)

