

SUZUKI PERFORMANCE NOTEBOOK

Shawnee, OK

Suzuki Marine

Test Date: 8-23-2015

Test Boat: Silver Wave 230 LP

Boat Type: Pontoon - Triple Log

DF200ATL



BOAT		ENGINE		OTHER SPECS	
Silver Wave 230LP		Suzuki DF200ATL		Propeller	
Material	Aluminum - 3 log	Engine Type	4 cylinder in-line	Material	Stainless Steel
Length	23' 10"	HP	200	Diameter/Pitch	16 X 20
Beam	8' 6"	Displacement	2867 cc's	Number of Blades	3
Weight	2200 lbs	Operating Range	5500 - 6100	Mounting Height	
Maximum HP	200	Weight	498 lbs	Hole Position	3rd Hole up
Fuel Capacity	46 gallons	Lubrication	Wet Sump	Jack Plate	N/A
Transom Height	20"	Fuel Delivery	Multi-Point EFI		
Steering	SeaStar Hydraulic	Ignition	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE	Water Conditions	Light Chop
IDLE	2.7	0.3	9.00	373	Wind Velocity	10-15 mph
1000	4.2	0.7	6.00	248	Air Temperature	90 degrees
1500	5.7	1.3	4.38	182	Fuel Load	35 gallons
2000	8.0	1.8	4.44	184	Weight Onboard	2 persons
2500	12.0	2.7	4.44	184		Full Safety Gear
3000	17.6	3.4	5.18	214	PERFORMANCE SUMMARY	
3500	21.5	4.6	4.67	194	Top Speed	45.1
4000	26.7	6.5	4.11	170	0-20 Acceleration	5.3
4500	32.9	7.8	4.22	175	Optimum Cruising	@ 3000 RPM
5000	36.8	10.8	3.41	141	Range	214 Miles
5500	41.1	12.6	3.26	135	Best Cruising	@ 3000 RPM
6000	45.1	17.8	2.53	105	Fuel Efficiency	5.18 MPG

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION, CONTACT:

Silver Wave Pontoons

Seminole, OK

(405) 382-0349

www.silverwaveboats.com

Suzuki Marine

www.suzuki.com

