

SUZUKI PERFORMANCE NOTEBOOK

Miami, FL

Suzuki Marine

Test Date: 2-20-2012

Test Boat: Glasstream

Boat Type: Center Console

Test Motor: Suzuki DF300APX



BOAT		ENGINE		OTHER SPECS	
2012 32 SCX		Suzuki DF300APX Dual Install		Propeller	
Material	Fiberglass	Engine Type	4-Stroke V-6	Material	Stainless Steel
Length	32'	HP	300 x 2 (600 HP)	Diameter/Pitch	15 x 26
Beam	8' 11"	Displacement	4.0L	Number of Blades	4
Weight	5300 lb.s	Operating Range	5700-6300	Mounting Height	
Maximum HP	600	Weight	604 lb.s	Hole Position	3rd Hole Up
Fuel Capacity	218 gallons	Lubrication	Wet Sump	Jack Plate	N/A
Transom Height	25	Fuel Delivery	Multi-Point EFI		
Steering	Hydraulic	Ignition	Solid State		

PERFORMANCE DATA						TEST CONDITIONS	
------------------	--	--	--	--	--	-----------------	--

RPM	MPH	GPH	MPG	RANGE	DB
IDLE	4.1	1.0	4.10	804	n/a
1000	5.7	2.3	2.48	486	n/a
1500	8.1	4.9	1.65	324	n/a
2000	9.8	7.5	1.31	256	n/a
2500	17.6	11.8	1.49	293	n/a
3000	20.7	12.3	1.68	330	n/a
3500	31.1	16.4	1.90	372	n/a
4000	36.7	20.8	1.76	346	n/a
4500	41.3	24.7	1.67	328	n/a
5000	50.4	32.7	1.54	302	n/a
5500	61.7	46.1	1.34	263	n/a
6100	66.2	56.4	1.17	230	n/a

Water Conditions	Light Chop
Wind Velocity	Light Breeze
Air Temperature	79 degrees
Fuel Load	110 gallons
Weight Onboard	2 persons Full Safety Gear

PERFORMANCE SUMMARY

Top Speed	66.2 mph
0-30 Acceleration	5.8 seconds
Optimum Cruising Range	372 Miles @ 3500
Best Cruising	1.90 MPG
Fuel Efficiency	@ 3500 RPM

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION, CONTACT:

Glasstream Boats
1143 East 15th Street
Panama City, FL 32405
www.glasstream.com

Suzuki Marine
714-996-7040
www.suzuki.com

