

SUZUKI PERFORMANCE NOTEBOOK

Jupiter, FL

Suzuki Marine

Test Date: 7-19-17

Test Boat: Twin Vee

Boat Type: Catamaran

Test Motor: Suzuki DF150APX



BOAT	ENGINE	OTHER SPECS
------	--------	-------------

260 SE	Suzuki DF150APX (Twin install)	Propeller
Material: Fiberglass	Engine Type: 4-Stroke 4-Inline	Material: Stainless Steel
Length: 25' 6"	HP: 300	Diameter/Pitch: 15.25 x 20
Beam: 8' 6"	Displacement: 174.9 ci	Number of Blades: 4
Weight: 3260 lb.s	Operating Range: 5500-6000	Mounting Height
Maximum HP: 350	Weight: 531 lb.s	Hole Position: 3rd
Fuel Capacity: 138 gallons	Lubrication: Wet Sump	Jack Plate: N/A
Transom Height: 25"	Fuel Delivery: Multi-Point EFI	
Steering: Hydraulic	Ignition: Solid State	

PERFORMANCE DATA	TEST CONDITIONS
------------------	-----------------

RPM	MPH	GPH	MPG	RANGE
IDLE	3.6	0.8	4.50	559
1000	5.1	1.4	3.64	452
1500	6.9	2.6	2.65	330
2000	8.6	3.7	2.32	289
2500	10.3	5.4	1.91	237
3000	17.1	6.9	2.48	308
3500	23.0	9.2	2.50	311
4000	27.4	11.7	2.34	291
4500	31.8	14.8	2.15	267
5000	36.1	17.5	2.06	256
5500	39.7	23.9	1.66	206
6000	42.2	26.0	1.62	202

Water Conditions	Calm
Wind Velocity	0-5 mph
Air Temperature	85 degrees
Fuel Load	100 gallons
Weight Onboard	3 person & Gear
	T-Top W/Hardtop
	2 Batteries

PERFORMANCE SUMMARY

Top Speed	42.2 mph
0-30 Acceleration	4.8 seconds
Optimum Cruising	311 Miles
Range	@ 3500
Best Cruising	2.50 MPG
Fuel Efficiency	@ 3500 RPM

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION, CONTACT:

Twin Vee Catamarans
3101 S US 1 Hwy
Fort Pierce, FL 34982
www.info@twinvee.com

Suzuki Marine
714-996-7040
www.suzuki.com

