



# PERFORMANCE NOTEBOOK

## SeaArk EasyCat



BOAT		ENGINE		OTHER SPECS	
<b>EasyCat</b>		<b>Suzuki DF300APX</b>		<b>Propeller</b>	
Material:	Aluminum	Engine Type:	4-Stroke 6Cyl.	Material:	Stainless
Length:	26'	HP:	300	Diameter/Pitch:	16 X 18.5
Beam:	7'11"	Displacement:	245.8cu. In.	Number of Blades:	3 Blade
Weight:	2000 lb.s	Operating Range:	5700-6300	<b>Mounting Height</b>	
Maximum HP:	300	Weight:	639 lb.s	Hole Position:	#2 Hole
Fuel Capacity:	67 gallons	Lubrication:	Wet Sump	Jack Plate:	N/A
Transom Height:	25"	Fuel Delivery:	Multi-Point EFI		
Steering:	Hydraulic	Ignition:	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE		
IDLE	3.8	0.5	7.60	458	Water Conditions:	Light Chop
1000	5.3	1.0	5.30	320	Wind Velocity:	5-10 mph
1500	7.9	2.0	3.95	238	Air Temperature:	56 F
2000	12.1	2.5	4.84	292	Fuel Load:	35 gal.
2500	17.8	3.8	4.68	282	Weight Onboard:	2 person/FSG*
3000	23.1	5.0	4.62	279	Test Date:	10/29/2022
3500	28.3	6.4	4.42	267	*Full Safety Gear	
4000	33.1	8.4	3.94	238	PERFORMANCE SUMMARY	
4500	37.5	11.4	3.29	198	Top Speed	51.2 MPH
5000	42.0	15.1	2.78	168	0-30 Acceleration	5.33 Seconds
5500	45.6	19.0	2.40	145	Optimum Cruising	2000 RPM
6000	49.3	24.3	2.03	122	Range	292 Miles
6200	51.2	26.4	1.94	117	Best Cruising	2000 RPM
Results may vary. Range based on 90% fuel capacity.					Fuel Efficiency	4.84 MPG

### FOR MORE INFORMATION CONTACT:

SeaArk Boats- Monticello, AR  
[www.seaarkboats.com](http://www.seaarkboats.com)  
 (870) 367-5317

SUZUKI MARINE USA LLC - Tampa, FL  
[www.suzukimarine.com](http://www.suzukimarine.com)  
 (813)687-7200