



PERFORMANCE NOTEBOOK

SeaArk Protégé



BOAT		ENGINE		OTHER SPECS	
Protégé		Suzuki DF200ATX		Propeller	
Material:	Aluminum	Engine Type:	4-Stroke 4Cyl.	Material:	Stainless
Length:	20'1"	HP:	200	Diameter/Pitch:	16 X 23
Beam:	7'10"	Displacement:	174.96cu. In.	Number of Blades:	3 Blade
Weight:	1300 lb.s	Operating Range:	5500-6100	Mounting Height	
Maximum HP:	200	Weight:	529 lb.s	Hole Position:	#2 Hole
Fuel Capacity:	51 gallons	Lubrication:	Wet Sump	Jack Plate:	N/A
Transom Height:	25"	Fuel Delivery:	Multi-Point EFI		
Steering:	Hydraulic	Ignition:	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE	Water Conditions:	Light Chop
IDLE	3.4	0.4	8.50	390	Wind Velocity:	5-10 mph
1000	5.0	0.7	7.14	328	Air Temperature:	81 F
1500	7.2	1.4	5.14	236	Fuel Load:	40 gal.
2000	10.1	2.0	5.05	232	Weight Onboard:	2 person/FSG*
2500	17.1	2.7	6.33	291	Test Date:	10/28/2022
3000	23.8	3.6	6.61	303	*Full Safety Gear	
3500	28.9	5.0	5.78	265	PERFORMANCE SUMMARY	
4000	33.7	6.9	4.88	224	Top Speed	50.3 MPH
4500	38.7	9.3	4.16	191	0-30 Acceleration	6.45 Seconds
5000	43.0	12.5	3.44	158	Optimum Cruising	3000 RPM
5500	47.5	16.9	2.81	129	Range	303 Miles
6000	50.3	18.0	2.79	128	Best Cruising	3000 RPM
					Fuel Efficiency	6.61 MPG

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION CONTACT:

SeaArk Boats- Monticello, AR
www.seaarkboats.com
 (870) 367-5317

SUZUKI MARINE USA LLC - Tampa, FL
www.suzukimarine.com
 (813)687-7200