



PERFORMANCE NOTEBOOK

SeaArk River Cat 2060 SC



BOAT		ENGINE		OTHER SPECS	
River Cat 2060 SC		Suzuki DF115BTLSS		Propeller	
Material:	Aluminum	Engine Type:	4-Stroke 4Cyl.	Material:	Stainless
Length:	20'1"	HP:	115	Diameter/Pitch:	14 X 23
Beam:	6'10"	Displacement:	124.7cu. In.	Number of Blades:	3 Blade
Weight:	1100 lb.s	Operating Range:	5000-6000	Mounting Height	
Maximum HP:	115	Weight:	415 lb.s	Hole Position:	#2 Hole
Fuel Capacity:	18 gallons	Lubrication:	Wet Sump	Jack Plate:	N/A
Transom Height:	20"	Fuel Delivery:	Multi-Point EFI		
Steering:	Hydraulic	Ignition:	Solid State		

PERFORMANCE DATA					TEST CONDITIONS	
RPM	MPH	GPH	MPG	RANGE	Water Conditions:	Light Chop
IDLE	3.0	0.3	10.00	162	Wind Velocity:	5-10 mph
1000	4.5	0.6	7.50	122	Air Temperature:	80 F
1500	6.4	1.1	5.82	94	Fuel Load:	18 gal.
2000	8.1	1.8	4.50	73	Weight Onboard:	2 person/FSG*
2500	11.8	2.7	4.37	71	Test Date:	10/28/2022
3000	17.9	3.2	5.59	91	*Full Safety Gear	
3500	23.6	4.6	5.13	83	PERFORMANCE SUMMARY	
4000	28.2	5.4	5.22	85	Top Speed	41.4 MPH
4500	33.3	7.8	4.27	69	0-25 Acceleration	5.5 Seconds
5000	36.3	10.0	3.63	59	Optimum Cruising	3000 RPM
5500	38.7	13.5	2.87	46	Range	91 Miles
6100	41.4	14.1	2.94	48	Best Cruising	3000 RPM
					Fuel Efficiency	5.59 MPG

Results may vary. Range based on 90% fuel capacity.

FOR MORE INFORMATION CONTACT:

SeaArk Boats- Monticello, AR
www.seaarkboats.com
 (870) 367-5317

SUZUKI MARINE USA LLC - Tampa, FL
www.suzukimarine.com
 (813)687-7200